



Laser Diode Driver & Dual TEC Controller

LPS1-2T Series

Microprocessor-
Controlled

The LPS1-2T is a very compact microprocessor-controlled laser diode driver with dual temperature controller. It offers many advanced and unique features at a very competitive price.

The device can drive up to three infrared laser diodes in series or one blue laser diode. Different models of the LPS1-2T are available, depending on the maximum laser diode current. All devices feature constant current as well as constant power modes. Current limits, voltage limits and a soft-start delay can be set. A safety interlock is also implemented.

The LPS1-2T is very easy to use. All parameters can be programmed through the symbolic self-explanatory controls. The two-line matrix display shows set values and actual values at the same time.

ALPHALAS has implemented a novel switch-mode topology to achieve high efficiency, low thermal dissipation and a very compact design. A unique combination of analog and digital control guarantees very low current noise and high reliability.



Features

- Microprocessor-Controlled with Fully Programmable Parameters and Two-Line Matrix Display
- Easy to Use with Self-Explanatory Operational Controls
- Current Limits, Voltage Limits, Soft-Start, Safety Interlock
- Very Low Current Noise
- High Reliability
- Const. Current & Const. Power Modes
- Drives Multiple Laser Diodes in Series
- Very Compact Design

Display Data

- Laser Diode Current
- Laser Diode Current Limit
- TEC Current 1 & 2
- TEC Current Limit 1 & 2
- Laser Diode Temperature 1 & 2
- Laser Diode Voltage
- Laser Diode Voltage Limit
- Operating Mode (Const. Current/ Const. Power)
- Optical Power (Relative Units)
- Soft-Start Delay (Relative Units)

LPS1-2T Series: Electrical Specifications

Voltage and Current Requirements	LPS1-2T: 12 V DC, 5 - 8 A Optional AC/DC Adapter: Universal Input, 100 - 240 V AC (<i>may differ, model dependent</i>)		
Power Consumption	Depends on the Laser, 50 - 100 W		
Conversion Accuracy	D/A: 12 bit, A/D: 12 bit		
Laser Diode Current (model dependent, other hardware current limit may be factory preset)	LPS1-2T-L	LPS1-2T-E	LPS1-2T-HP
	0 - 2.5 A	0 - 4.0 A	0 - 8.0 A
Laser Diode Voltage (model dependent, programmable)	max. 7 V	max. 6.5 V	max. 6 V
Current Noise, rms	60 µA		
TEC Controllers	Two Controllers, 4 A, 8 V each, cooling mode only		
TEC Temperature Range (programmable)	TEC 1: 0°C - 99.9°C (hardware high temperature limit can be factory preset, default is 38°C) TEC 2: 0°C - 99.9°C (no hardware high temperature limit)		
Temperature Stability	0.1°C		
Remote Control	Proprietary PC Serial Interface		

LPS1-2T Series: Mechanical Specifications

LPS1-2T Dimensions	105 x 70 x 200 mm ³ (WxHxL)
Optional AC/DC Adapter Dimensions	100 x 67 x 32 mm ³ (WxHxL) (<i>may differ, model dependent</i>)
Ambient Temperature	5°C .. 35°C (41°F .. 95°F)

ALPHALAS GMBH
 Bertha-von-Suttner-Str. 5
 D-37085 Goettingen
 Germany

TEL +49 - 551 - 77 06 147
 FAX +49 - 551 - 77 06 146
 E-MAIL sales@alphalas.com
 WEB www.alphalas.com

LASERS, OPTICS, ELECTRONICS.
 MADE IN GERMANY.
WWW.ALPHALAS.COM



Options and further specifications are available upon request. Specifications in this data sheet are subject to change without notice. We reserve the right to make any changes that do not deteriorate the specified performance of our products. No responsibility for typing or printing errors. • Please note: Our products are intended for expert users only. They must not be used where injury to persons or damage to property may occur. Our products must not be used for medical or any other *in vivo* applications. They must not be used in critical applications (e.g. in life support systems, in aviation, in nuclear facilities, in weapon systems, in safety or security systems, etc.).