



gentec-e)

QE65LP-S-MB-D0

Pyroelectric detector for laser energy measurement up to 50 J.



PRODUCT FAMILY KEY FEATURES

MODULAR CONCEPT

Increase the power capability of your detector: 2 different cooling modules

LARGE APERTURE Effective aperture of 65 x 65 mm

QED ATTENUATOR AVAILABLE

Measure up to 5X higher energies. Available with optional calibration, all wavelengths between 532 & 1064 nm, or single wavelength. Read mo

LOW NOISE LEVEL 10 µJ for the MB coating

TEST TARGET INCLUDED With the MB models

SMART INTERFACE Containing all the calibration data

COMPATIBLE STAND

STAND-D-233

SPECIFICATIONS

MEASUREMENT CAPABILITIES

Spectral range ¹	0.193 - 20 μm
Typical rise time	1 ms
Repeatability	<0.5%
Maximum repetition frequency	100 Hz
Maximum measurable energy ²	50 J
Noise equivalent energy ³	10 µJ
Maximum pulse width	0.7 ms
Energy calibration uncertainty	±3 %
1. For the calibrated spectral range, see the user manual	

1. For the calibrated spectral range, see the user manual.

2. At 1064 nm, 150 $\mu s,$ single-shot. Increasing pulse width increases maximum measurable energy. 3. Nominal value. Actual value depends on electrical noise in the measurement system.

DAMAGE THRESHOLDS

Maximum average	power	density ¹
-----------------	-------	----------------------

Maximum average power density ¹	10 W/cm ²
Maximum energy density ²	0.6 J/cm²
Maximum power	12 W

1. May vary with wavelength and average power. 2. At 1064 nm, 7 ns, 10 Hz. May vary with wavelength and pulse width.

PHYSICAL CHARACTERISTICS

Cooling	Convection
Aperture width	65 mm
Aperture height	65 mm
Absorber	МВ
Dimensions	92H x 92W x 20D mm
Weight	0.44 kg

ORDERING INFORMATION

OE65LP-S-MB-D0





Instrument Expert Original factory packaging www.dorgean.com

QE65LP-S-MB-INT-D0 QE65LP-S-MB-INE-D0

QE65LP-S-MB-IDR-D0

203296

202766

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us