



# UP55M-50W-W9-D0

Thermal detector for laser power measurement up to 50 W.



## PRODUCT FAMILY KEY FEATURES

- MODULAR CONCEPT**  
Increase the power capability of your detector: 4 different cooling modules
- VERY HIGH DAMAGE THRESHOLD**  
100 kW/cm<sup>2</sup> in average power density
- VERY LARGE APERTURE**  
55 mm effective aperture diameter, perfect for the largest beams
- HIGHEST ENERGY READINGS IN THE SERIES**  
Measure single shot energy up to 500 J
- SMART INTERFACE**  
Containing all the calibration data
- COMPATIBLE STAND**  
[STAND-S-443](#)



## SPECIFICATIONS

### MEASUREMENT CAPABILITIES

Maximum average power (continuous) <sup>1</sup>	50 W
Maximum average power (1 minute) <sup>2</sup>	85 W
Noise equivalent power <sup>3</sup>	5 mW
Spectral range <sup>4</sup>	0.193 - 10 μm
Typical rise time <sup>5</sup>	3.5 s
Power calibration uncertainty <sup>6</sup>	±2.5 %
Repeatability	±0.5 %

1. Minimum cooling flow 1 liters/min, water temperature ≤ 22°C, 1/8 NPT compression fittings for 1/4 inch semi-rigid tube. Contact Gentec-EO for clean deionized water cooling module option.
2. Minimum cooling flow 1 liters/min, water temperature ≤ 22°C, 1/8 NPT compression fittings for 1/4 inch semi-rigid tube. Contact Gentec-EO for clean deionized water cooling module option.
3. Nominal value, actual value depends on electrical noise in the measurement system.
4. For the calibrated spectral range, see the user manual.
5. With anticipation.
6. Including linearity with power.

### MEASUREMENT CAPABILITIES (ENERGY MODE)

Typical energy sensitivity	0.02 mV/J
Maximum measurable energy <sup>1</sup>	500 J
Noise equivalent energy <sup>2</sup>	0.25 J
Minimum repetition period	11.1 s
Maximum pulse width	467 ms
Energy calibration uncertainty <sup>3</sup>	±5 %

1. For 360 μs pulses. Higher pulse energy possible for long pulses (ms), less for short pulses (ns).
2. Nominal value, actual value depends on electrical noise in the measurement system.
3. When single-shot energy calibration is purchased

### DAMAGE THRESHOLDS

Maximum average power density <sup>1</sup>	100 kW/cm <sup>2</sup>
Maximum energy density <sup>2</sup>	1.1 J/cm <sup>2</sup>

1. At 1064 nm, 10 W CW. May vary with wavelength and average power.



2. At 1064 nm, 7 ns, 10 Hz. May vary with wavelength and pulse width.

PHYSICAL CHARACTERISTICS

Cooling	Water
Aperture diameter	55 mm
Absorber	W
Dimensions	119H x 89W x 46D mm
Weight	0.81 kg

ORDERING INFORMATION

UP55M-50W-W9-D0	205345
UP55M-50W-W9-INT-D0	205350
UP55M-50W-W9-BLU-D0	205357
UP55M-50W-W9-IDR-D0	205351

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at [gentec-eo.com/contact-us](http://gentec-eo.com/contact-us)