



CVM-780 Contact Voltmeter

The New CVM-780 Contact Voltmeter™ combines the ease of use of a digital voltmeter with the high input impedance and low input capacitance of a true electrostatic voltmeter in a small, portable, battery operated package.

Being a true electrostatic voltmeter, not a field meter means that it reads real voltage, without confusing it with electrostatic field strength, which can be distinctly different.

Specifications

- Basic Description:** High impedance contact voltmeter with active probe
- DC Characteristics:** Intended Operating Range: 0 to ± 525 volts
Resolution: 1 volt, 3 digit display
Circuit accuracy: $< \pm 1\%$
Note: Maximum measurement range is ± 575 Volts for brief periods
- Dynamic Characteristics:** Response Time: Approximately 1ms for a voltage step of 200V at the probe tip to the monitor output.
Digital display update: 3 readings per second.
- Input charge/measurement:** Approximately 100 femptocoulomb/volt (1.0×10^{-13} C/V)
- Input Impedance:** $\geq 10^{14}$ ohm in parallel with < 1 pF Capacitance
- Monitor Output:** Scale Factor: 10,000:1; 100uV/V (Compatible with Prostat™ PGA-710 Autoanalysis System™)
Recording Deviation: Typically $< \pm 10$ volts at ± 500 Volts
- Measurement Tolerances:** When measuring DC voltage reference

500 V $\leq \pm 2$ V
100 V $\leq \pm 2$ V
50 V $\leq \pm 2$ V
10 V $\leq \pm 1$ V



When measuring floating conductors:

500 V $\leq \pm 5\%$ ± 2 Counts
100 V $\leq \pm 5\%$ ± 2 Counts
50 V $\leq \pm 5\%$ ± 2 Counts
10 V $\leq \pm 10\%$ ± 2 Counts

Probe Tips:	Metal: Nominally 0.95 and 0.45 inch Ceramic 0.90 and 0.40 inch ± 0.05 "
Portable Operation:	Approximately 3.5 Hours on Full Battery Charge (Operates during Battery Charge)
Power:	4 each Energizer NH15-2500 Nickel-Metal Hydride rechargeable batteries (AA Size)
Charger:	Universal 90 to 264 Volts, 47 to 63 Hz
Meter Dimension (without boot):	6.5 in (16.5 cm) L x 4.25 in (10.8 cm) W x 1.57 in (4.0 cm) H
Meter Dimension (with boot):	7.5 in (19.1 cm) L x 4.25 in (10.8 cm) W x 2.36 in (6.0 cm) H
Probe Dimension:	8.9 in (22.5 cm) L x 1.5 in (3.7 cm) W x 0.78 in (2.0 cm) H
Meter Weight:	1.5 lbs, with boot
Probe Weight:	3.6 oz

©2008 Prostat Corporation. All rights reserved.
 Prostat is the registered trademarks of Prostat Corporation in the United States and other countries.

1072 Tower Lane, Bensenville, IL 60106 USA
 Phone +1 (630) 238-8883 Fax +1 (630) 238-9717
 Web access: <http://www.prostatcorp.com>

Specifications subject to change without notice.
 Printed in U.S.A. REV1: 4/14/08